# NSN 5320-01-469-2860

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-469-2860



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.948 inches and 0.968 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.122 inches and 0.142 inches

## Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

## **End Application:**

F-18 e/f

# Grip Length:

Between 0.558 inches and 0.568 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## **Countersink Angle:**

100.0 degrees

## **Product Name:**

Pin-rivet, threaded, shear, 100 degree c'sunk head, hex poin

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A528u0