
## NSN 5320-01-469-2948

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.098 inches and 1.118 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

#### Lubrication:

Solid film and cetyl alcohol

#### **End Application:**

F18 de/f

## Grip Length:

Between 0.558 inches and 0.568 inches

## Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### **Countersink Angle:**

100.0 degrees

#### **Criticality Code Justification:**

Agav

#### **Product Name:**

Pin-rivet, threded, shear, 100 degree c'sunk head, hex point drive

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Ams qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-469-2948

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

