NSN 5320-01-469-2950

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-469-2950

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.035 inches and 1.055 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5554 inches and 0.5604 inches
Lubrication:
Solid film and cetyl alcohol
End Application:
F18 de/f
Grip Length: Between 0.495 inches and 0.505 inches
Thready Qty Per Inch (tpi):
Thread Size:
0.375 inches
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Agav
Product Name:
Pin-rivet, threded, shear, 100 degree c'sunk head, hex point drive
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-469-2950

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0