

View Online at <https://aerobasegroup.com/nsn/5320-01-469-2950>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.035 inches and 1.055 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

Lubrication:

Solid film and cetyl alcohol

End Application:

F18 de/f

Grip Length:

Between 0.495 inches and 0.505 inches

Thread Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

100.0 degrees

Criticality Code Justification:

Agav

Product Name:

Pin-riquet, threaded, shear, 100 degree c'sunk head, hex point drive

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0