

View Online at <https://aerobasegroup.com/nsn/5320-01-469-7215>

**Fastener Length:**

0.725 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

0.190 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.349 inches and 0.357 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Prowler ea-6b aircraft

**Grip Length:**

Between 0.501 inches and 0.562 inches

**Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

**Product Name:**

Rivet, blind, -general purpose, bulbed, 100 degree flush head, mechanically locked spindle

**Special Features:**

Locking ring-passivate per qq-p-35 for cres only; intended for general purpose use in both thick sheet stack-up and in thin sheet or double dimpled applications; block 89 upgrade

**Material:**

Iron alloy 660 stem

**Material Specification:**

Qq-n-282 federal specification single material response sleeve

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-416, type2, class3 federal specification single treatment response sleeve or nas4006 assn standard single treatment response sleeve

**Specification Data:**

80205-nas1921 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0