

View Online at <https://aerobasegroup.com/nsn/5320-01-469-7215>

Fastener Length:

0.725 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

0.190 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.349 inches and 0.357 inches

Expansion Device:

Serrated stem-type w

End Application:

Prowler ea-6b aircraft

Grip Length:

Between 0.501 inches and 0.562 inches

Countersink Angle:

Between 98.5 degrees and 101.5 degrees

Product Name:

Rivet, blind, -general purpose, bulbed, 100 degree flush head, mechanically locked spindle

Special Features:

Locking ring-passivate per qq-p-35 for cres only; intended for general purpose use in both thick sheet stack-up and in thin sheet or double dimpled applications; block 89 upgrade

Material:

Iron alloy 660 stem

Material Specification:

Qq-n-282 federal specification single material response sleeve

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-416, type2, class3 federal specification single treatment response sleeve or nas4006 assn standard single treatment response sleeve

Specification Data:

80205-nas1921 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0