NSN 5320-01-469-8565

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-469-8565 **Thread Class:** 3b **Thread Direction:** Right-hand Fastener Length: 1.500 inches **Head Style:** Err-090 **Head Height:** 0.156 inches **Shank Diameter:** 1.008 inches **Head Major Diameter:** 1.200 inches **End Application:** Mh-47e special operations hekicopter Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Product Name:** Pin, aft rotor shaft **Special Features:** length 2.00inches ly; underhead length to chamfered threaded end is 1.72 inches ly; end item is cargo helicopter; all diameters on a common centerline to be concentric to each other within .010 diameter unless otherwise noted; break all sharp edges; all threads per mil-s-8879; heat treat in accordance with bac 5617 to 150-170 ksi uts **Heat Treatment:** Normalized and tempered Material: Steel comp 4340 **Material Specification:** Mil-s-5000, conde military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Bac5701 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5320-01-469-8565

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.