

View Online at <https://aerobasegroup.com/nsn/5320-01-471-5051>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.068 inches and 1.093 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.120 inches and 0.132 inches

**Shank Diameter:**

0.4563 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.669 inches and 0.685 inches

**Tip Diameter:**

0.4454 inches

**Lubrication:**

Dry film and cetyl alcohol

**Grip Length:**

Between 0.615 inches and 0.630 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Thread Size:**

0.437 inches

**Shear Strength:**

125000 single pounds per square inch

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0