## NSN 5320-01-471-5051

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-471-5051 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.068 inches and 1.093 inches **Head Style:** Err-090 **Head Height:** Between 0.120 inches and 0.132 inches **Shank Diameter:** 0.4563 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.669 inches and 0.685 inches Tip Diameter: 0.4454 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.615 inches and 0.630 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.437 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:** Qq-p-35 federal specification single treatment response

**Passivate Surface Treatment Specification: Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5320-01-471-5051

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0