## NSN 5320-01-471-5053

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-471-5053



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.131 inches and 1.156 inches

## Head Style:

Err-090

## Head Height:

Between 0.120 inches and 0.132 inches

## Shank Diameter:

0.4563 inches

## Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

Between 0.669 inches and 0.686 inches

#### Tip Diameter:

0.4441 inches

## Lubrication:

Dry film and cetyl alcohol

## Grip Length:

Between 0.677 inches and 0.692 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

220000 pounds per square inch

## **Thread Size:**

0.437 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp xm-13

## **Material Specification:**

Ams5629 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

# NSN 5320-01-471-5053

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

