NSN 5320-01-471-5534

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-471-5534 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.271 inches and 1.296 inches **Head Style:** Err-090 **Head Height:** Between 0.082 inches and 0.094 inches **Shank Diameter:** 0.4068 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.628 inches and 0.642 inches Tip Diameter: 0.4062 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.865 inches and 0.880 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-471-5534

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0