# NSN 5320-01-471-6691

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-471-6691



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.802 inches and 1.827 inches

# Head Style:

Err-090

#### **Head Height:**

Between 0.165 inches and 0.177 inches

#### Shank Diameter:

0.3027 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.688 inches and 0.702 inches

#### Tip Diameter:

0.4297 inches

#### Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

Between 1.245 inches and 1.255 inches

# Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Thread Size:**

0.375 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response

# Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-471-6691

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

