## NSN 5320-01-471-6692

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-471-6692 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.365 inches and 1.390 inches **Head Style:** Err-090 **Head Height:** Between 0.165 inches and 0.177 inches **Shank Diameter:** 0.3027 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.688 inches and 0.702 inches Tip Diameter: 0.4388 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.802 inches and 0.817 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response

Thread Series Designator: Unjf

Shelf Life:

N/a

## NSN 5320-01-471-6692

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0