# NSN 5320-01-472-4283

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-472-4283

### Fastener Length:

1.430 inches

#### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### Shank Diameter:

Between 0.310 inches and 0.312 inches

#### Shank Style:

Self-plugging mechanically locked stem

### Head Major Diameter:

0.634 inches

**Expansion Device:** 

Serrated stem-type w

#### **End Application:**

Vertical stabilizer; f/a-18e/f hornet aircraft

#### Grip Length:

Between 0.906 inches and 0.970 inches

#### Min. Tensile Strength (psi):

5200 pounds per square inch

#### Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

#### Shear Strength:

8500 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

Material:

Steel stem

#### **Material Specification:**

Astm-a-331 assn standard single material response stem

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Mil-c-83488 military specification single treatment response

#### **Specification Data:**

96906-ms90353 government specification

#### Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A040a0

# NSN 5320-01-472-4283

Blind Rivet - Page 2 of 2

## Mil-std (military Standard):

Mil-c-83488 spec.

