# NSN 5320-01-472-4466

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-472-4466

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.1970 inches and 0.1985 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

0.385 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Dry film or cetyl alcohol or paraffin wax

#### **End Application:**

Vertical stab, f/a-18e/f hornet aircraft

#### Grip Length:

Between 0.300 inches and 0.350 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

For sealant application only, expose two to four threads

# Material:

Titanium alloy uns r56400 nut

## **Material Specification:**

Ams5732 assn standard single material response bolt or ams5731 assn standard single material response bolt or ams5737 assn standard

single material response bolt

#### Surface Treatment:

Passivate sleeve

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A040a0