NSN 5320-01-472-4478

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-472-4478 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.135 inches and 1.155 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.010 inches and 0.015 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches **Head Minor Diameter:** Between 0.375 inches and 0.388 inches **Countersink Height:** Between 0.0623 inches and 0.0694 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Aluminum

Surface Treatment:

NSN 5320-01-472-4478

Pin-rivet - Page 2 of 2



Hi-shear spec.No.29 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0