

View Online at <https://aerobasegroup.com/nsn/5320-01-472-4481>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.5025 inches and 0.5225 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.2021 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Head Minor Diameter:

Between 0.282 inches and 0.295 inches

Countersink Height:

Between 0.049 inches and 0.057 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 0.1825 inches and 0.1925 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1, specification 294, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0