## NSN 5320-01-472-4482

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-472-4482 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.565 inches and 0.585 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches **Head Minor Diameter:** Between 0.282 inches and 0.295 inches **Countersink Height:** Between 0.049 inches and 0.057 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400

**Material Specification:** 

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

**Surface Treatment:** 

Aluminum

**Surface Treatment Specification:** 

Hi-kote 1, specification 294, cage 73197 mfr ref single treatment response

## NSN 5320-01-472-4482

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0