NSN 5320-01-472-4665



Blind Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-472-4665 Fastener Length: 0.678 inches **Head Style:** Tapered pan **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.258 inches and 0.260 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.400 inches and 0.432 inches **Expansion Device:** Serrated stem-type w **End Application:** Vertical stabilizer; f/a-18e/f hornet aircraft **Grip Length:** Between 0.219 inches and 0.282 inches Min. Tensile Strength (psi): 3650 pounds per square inch Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 8500 single pounds per square inch Material: Steel stem **Material Specification:** Astm-a-331 assn standard single material response stem **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488 military specification single treatment response **Specification Data:** 96906-ms90354 government specification Shelf Life:

N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0

NSN 5320-01-472-4665

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.