## NSN 5320-01-472-5856

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-472-5856 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.065 inches and 1.085 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.2177 inches and 0.2182 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3253 inches and 0.3303 inches **Head Minor Diameter:** Between 0.3110 inches and 0.3232 inches **Countersink Height:** Between 0.0550 inches and 0.0620 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Aluminum

**Surface Treatment:** 

## NSN 5320-01-472-5856

Pin-rivet - Page 2 of 2



Surface Treatment Speci
-------------------------

Hi-kote 1, specification 294, cage 73197 mfr ref single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0