NSN 5320-01-472-5859



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-472-5859 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.690 inches and 0.710 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches **Head Minor Diameter:** Between 0.282 inches and 0.295 inches **Countersink Height:** Between 0.049 inches and 0.057 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

NSN 5320-01-472-5859

Pin-rivet - Page 2 of 2



	Surface	Treatment	Specification:
--	---------	------------------	----------------

Hi-kote 1, specification 294, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0