

View Online at <https://aerobasegroup.com/nsn/5320-01-472-6283>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.135 inches and 1.155 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corporation and solid film

**End Application:**

Vertical stab, f/a-18e/f hornet aircraft

**Grip Length:**

Between 0.245 inches and 0.255 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Agav

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-+2-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0