NSN 5320-01-472-6484

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-472-6484

Fastener Length:

0.323 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Expansion Device:

Serrated stem-type w

End Application:

Vertical stab, f/a-18e/f hornet aircraft

Grip Length:

Between 0.063 inches and 0.125 inches

Shear Strength:

450 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

H-38 strain hardened locking ring

Material:

Aluminum alloy 5056 locking ring

Material Specification:

Qq-a-430 federal specification single material response locking ring

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

```
---
```

```
Demilitarization:
```

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.