

View Online at <https://aerobasegroup.com/nsn/5320-01-472-6491>

**Fastener Length:**

0.323 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Vertical stab, f/a-18e/f hornet aircraft

**Grip Length:**

Between 0.063 inches and 0.125 inches

**Shear Strength:**

450 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Heat Treatment:**

H-38 strain hardened locking ring

**Material:**

Aluminum alloy 5056 locking ring

**Material Specification:**

Qq-a-430 federal specification single material response locking ring

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.