## NSN 5320-01-472-6818

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-472-6818 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.053 inches and 1.073 inches **Head Style:** Flush countersunk **Head Height:** Between 0.068 inches and 0.070 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style: Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film **End Application:** Vertical stab, f/a-18e/f hornet aircraft **Grip Length:** Between 0.558 inches and 0.563 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment Specification:** Qq-+2-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-472-6818

Pin-rivet - Page 2 of 2



Fiig:

A528u0