## NSN 5320-01-472-7218

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-472-7218 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.285 inches and 1.305 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.7556 inches and 0.7604 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film **End Application:** Vertical stab, f/a-18e/f hornet aircraft **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-+2-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-472-7218

Pin-rivet - Page 2 of 2



Fiig:

A528u0