## NSN 5320-01-472-7314

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-472-7314

0.558 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.2020 inches and 0.2025 inches Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.2966 inches and 0.3016 inches Expansion Device: Expander Lubrication: Dry film Grip Length: Between 0.094 inches and 0.156 inches Countersink Angle: 100.0 degrees Material: Titanium alloy uns r56400 nut Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut Surface Treatment: Passivate nut Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut Shelf Life: N/a
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  Shank Diameter:  Between 0.2020 inches and 0.2025 inches  Shank Style:  Threaded self-plugging shank w/sleeve  Head Major Diameter:  Between 0.2966 inches and 0.3016 inches  Expansion Device:  Expansion Device:  Expander  Lubrication:  Dry film  Grip Length:  Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Shank Diameter: Between 0.2020 inches and 0.2025 inches Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.2966 inches and 0.3016 inches Expansion Device: Expander Lubrication: Dry film Grip Length: Between 0.094 inches and 0.156 inches Countersink Angle: 100.0 degrees Material: Titanium alloy uns r56400 nut Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut Surface Treatment: Passivate nut Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut Shelf Life:
Between 0.2020 inches and 0.2025 inches  Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.2966 inches and 0.3016 inches  Expansion Device: Expander Lubrication: Dry film  Grip Length: Between 0.094 inches and 0.156 inches  Countersink Angle: 100.0 degrees  Material: Titanium alloy uns r56400 nut  Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment: Passivate nut  Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut Shelf Life:
Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.2966 inches and 0.3016 inches Expansion Device: Expander Lubrication: Dry film Grip Length: Between 0.094 inches and 0.156 inches Countersink Angle: 100.0 degrees Material: Titanium alloy uns r56400 nut Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut Surface Treatment: Passivate nut Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut Shelf Life:
Threaded self-plugging shank w/sleeve  Head Major Diameter:  Between 0.2966 inches and 0.3016 inches  Expansion Device:  Expander  Lubrication:  Dry film  Grip Length:  Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Head Major Diameter: Between 0.2966 inches and 0.3016 inches  Expansion Device:  Expander  Lubrication: Dry film  Grip Length: Between 0.094 inches and 0.156 inches  Countersink Angle: 100.0 degrees  Material: Titanium alloy uns r56400 nut  Material Specification: Arms 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment: Passivate nut  Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut Shelf Life:
Between 0.2966 inches and 0.3016 inches  Expansion Device:  Expander  Lubrication:  Dry film  Grip Length:  Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Arms 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Expansion Device:  Expander  Lubrication:  Dry film  Grip Length:  Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Expander  Lubrication: Dry film  Grip Length: Between 0.094 inches and 0.156 inches  Countersink Angle: 100.0 degrees  Material: Titanium alloy uns r56400 nut  Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment: Passivate nut  Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut Shelf Life:
Lubrication:  Dry film  Grip Length:  Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Dry film  Grip Length: Between 0.094 inches and 0.156 inches  Countersink Angle: 100.0 degrees  Material: Titanium alloy uns r56400 nut  Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment: Passivate nut  Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut  Shelf Life:
Grip Length:  Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Between 0.094 inches and 0.156 inches  Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Countersink Angle:  100.0 degrees  Material:  Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Material: Titanium alloy uns r56400 nut  Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment: Passivate nut  Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut  Shelf Life:
Material: Titanium alloy uns r56400 nut  Material Specification: Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment: Passivate nut  Surface Treatment Specification: Qq-p-35 federal specification single treatment response nut  Shelf Life:
Titanium alloy uns r56400 nut  Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Material Specification:  Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut  Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Surface Treatment:  Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Passivate nut  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Surface Treatment Specification:  Qq-p-35 federal specification single treatment response nut  Shelf Life:
Qq-p-35 federal specification single treatment response nut  Shelf Life:
Shelf Life:
N/a
TVA
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A040a0