## NSN 5320-01-472-7315

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-472-7315



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.698 inches and 0.718 inches

## Head Style:

Err-090

#### Head Height:

Between 0.010 inches and 0.015 inches

## Width Between Flats:

Between 0.122 inches and 0.142 inches

#### Shank Diameter:

Between 0.2646 inches and 0.2651 inches

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Head Minor Diameter:

Between 0.375 inches and 0.388 inches

## **Countersink Height:**

Between 0.0623 inches and 0.0694 inches

## Lubrication:

Cetyl alcohol

#### End Application:

C-17

#### Grip Length:

Between 0.308 inches and 0.318 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## **Countersink Angle:**

100.0 degrees

## **Product Name:**

Pin-rivet, threaded

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams4967 assn standard single material response or ams4928 assn standard single material response

## Surface Treatment:

Aluminum

#### **Surface Treatment Specification:**

Hi-shear spec.No.29 (hi-kote 1 only) mfr ref single treatment response

# NSN 5320-01-472-7315

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

