# NSN 5320-01-472-7519

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-472-7519



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.065 inches and 1.085 inches

# Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

# Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and dry film

#### **End Application:**

Vertical stab, f/a-18e/f hornet aircraft

# Grip Length:

Between 0.745 inches and 0.755 inches

# Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp xm-13

## **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-+2-35 federal specification single treatment response

## **Thread Series Designator:**

Unjc

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-472-7519

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

