NSN 5320-01-472-7812

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-472-7812



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.678 inches and 0.698 inches

Head Style:

Err-090

Head Height:

Between 0.102 inches and 0.112 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Grease film or cetyl alcohol, specification 305, hi-shear corp

End Application:

Vertical stab, f/a-18e/f hornet aircraft

Grip Length:

0.188 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

950000 single pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Anodize

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-472-7812

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

