# NSN 5320-01-474-5216

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-474-5216



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.540 inches and 0.560 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2172 inches and 0.2182 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.120 inches and 0.130 inches

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp 431

## Material Specification:

Mil-s-18732 military specification single material response

### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416-ty ii, cl 2 federal specification single treatment response

# Thread Series Designator:

Unjf

Shelf Life:

N/a

### Unit Of Measure:

--

# NSN 5320-01-474-5216

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

