## NSN 5320-01-474-6219

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-474-6219

<b>Fastener</b>	I an	ath:
rastener	Len	uuı.

Between 1.705 inches and 1.725 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.155 inches and 0.158 inches

**Shank Style:** 

Straight w/radius chamfered tip

**Head Major Diameter:** 

Between 0.208 inches and 0.210 inches

**Countersink Angle:** 

Between 118.5 degrees and 121.5 degrees

**Special Features:** 

Chemical surface treatment per mil-c-5541, class 1a; heat treatment in accordance with mil-h-6088 for aluminum alloys

Material:

Aluminum alloy 2117

**Material Specification:** 

Qq-a-430 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type ii, class 1, dichromate seal at 208-212 degrees f military specification single treatment response

**Specification Data:** 

80205-nas14218 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_

Demilitarization:

No

Fiig: A040a0

Mil-std (military Standard):

Mil-a-8625 spec.