# NSN 5320-01-474-6219

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-474-6219

# Fastener Length:

Between 1.705 inches and 1.725 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.155 inches and 0.158 inches

# Shank Style:

Straight w/radius chamfered tip

# Head Major Diameter:

Between 0.208 inches and 0.210 inches

# **Countersink Angle:**

Between 118.5 degrees and 121.5 degrees

# Special Features:

Chemical surface treatment per mil-c-5541, class 1a; heat treatment in accordance with mil-h-6088 for aluminum alloys

#### Material:

Aluminum alloy 2117

## **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type ii, class 1, dichromate seal at 208-212 degrees f military specification single treatment response

## **Specification Data:**

80205-nas14218 professional/industrial association standard

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.