

View Online at <https://aerobasegroup.com/nsn/5320-01-474-6250>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.325 inches and 1.360 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3891 inches and 0.3901 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.571 inches and 0.576 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C5 acft; aircraft, galaxy c-5

Grip Length:

Between 0.745 inches and 0.760 inches

Thread Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.