## NSN 5320-01-475-7831

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-475-7831 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 2.3150 inches and 2.3350 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Solid film or dry film **Grip Length:** Between 1.9950 inches and 2.0050 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:** 

Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-475-7831

Pin-rivet - Page 2 of 2



Fiig:

A528u0