NSN 5320-01-475-8072

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-475-8072 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.6700 inches and 0.6900 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.345 inches and 0.352 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.3700 inches and 0.3800 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:

NSN 5320-01-475-8072

Pin-rivet - Page 2 of 2



Fiig:

A528u0