# NSN 5320-01-475-8074

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-475-8074



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.7950 inches and 0.8150 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.345 inches and 0.352 inches

#### Lubrication:

Dry film and cetyl alcohol

### Grip Length:

Between 0.4950 inches and 0.5050 inches

# Thready Qty Per Inch (tpi):

32

## Thread Size:

0.1900 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-475-8074

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

