NSN 5320-01-475-8079

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-475-8079



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.0900 inches and 1.1100 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.470 inches and 0.477 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

Between 0.7450 inches and 0.7550 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.2500 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-475-8079

Pin-rivet - Page 2 of 2

Fiig: A528u0

