# NSN 5320-01-475-8082

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-475-8082



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.2150 inches and 1.2350 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.470 inches and 0.477 inches

#### Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

Between 0.8700 inches and 0.8800 inches

# Thready Qty Per Inch (tpi):

28

#### **Thread Size:**

0.2500 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-475-8082

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

