## NSN 5320-01-475-8082

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-475-8082 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.2150 inches and 1.2350 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.470 inches and 0.477 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.8700 inches and 0.8800 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

-- **Demilitarization:** No

## NSN 5320-01-475-8082

Pin-rivet - Page 2 of 2



Fiig:

A528u0