NSN 5320-01-475-8088

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-475-8088 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.7775 inches and 0.7975 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.470 inches and 0.477 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.4325 inches and 0.4425 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:
No

NSN 5320-01-475-8088

Pin-rivet - Page 2 of 2



Fiig:

A528u0