NSN 5320-01-475-8141

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-475-8141 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.495 inches and 0.505 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.358 inches and 0.365 inches Lubrication: Solid film or dry film and cetyl alcohol **Grip Length:** Between 0.842 inches and 0.862 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** Between 99.5 degrees and 100.5 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5320-01-475-8141

Pin-rivet - Page 2 of 2



Fiig:

A528u0