

View Online at <https://aerobasegroup.com/nsn/5320-01-475-8277>

**Fastener Length:**

0.349 inches

**Head Style:**

Brazier

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.125 inches and 0.129 inches

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.188 inches and 0.250 inches

**Product Name:**

Rivet-blind, protruding head, mechanically locked spindle, bulbed style a, class 1, code b and e

**Special Features:**

Lube in accordance with nas 1686; lock ring material applicable to visible lock type only; cad plating for (e) coded rivets with cres spindle provides lubricity only and is not necessary for corrosion/galvanic protection; spindle diameter not to exceed rivet diameter

**Material:**

Steel comp 632 stem or iron alloy 660 stem

**Material Specification:**

Ams5731 assn standard 1st material response locking ring or ams5639 assn standard 2nd material response locking ring

**Surface Treatment:**

Passivate locking ring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response locking ring

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.