

View Online at <https://aerobasegroup.com/nsn/5320-01-476-1040>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.815 inches and 0.835 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.010 inches and 0.015 inches

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.2021 inches and 0.2026 inches

**Shank Style:**

**Head Major Diameter:**

Between 0.2966 inches and 0.3016 inches

**Head Minor Diameter:**

Between 0.282 inches and 0.295 inches

**Countersink Height:**

Between 0.049 inches and 0.057 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17 aircraft

**Grip Length:**

Between 0.495 inches and 0.505 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.1900 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet, threaded

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4967 assn standard single material response or aams 4928 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Per hi-shear specification no 29 (hi-kote 1 only) mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0