

View Online at <https://aerobasegroup.com/nsn/5320-01-476-1515>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.875 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.045 inches and 0.060 inches

**Shank Diameter:**

Between 0.163 inches and 0.164 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.242 inches and 0.262 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

Tactical vehicles

**Grip Length:**

0.563 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Shear Strength:**

1760 double pounds per square inch

**Product Name:**

Pin-riquet threaded, protruding head, hex point drive

**Special Features:**

Tension pounds 949; heat treat age to t6 condition per mil-h-6088; finish dye natural; dimensions after finish; surface texture per ansi b46.1 and hole preparation per hp3-2

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.