

View Online at <https://aerobasegroup.com/nsn/5320-01-476-1515>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.875 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.060 inches

Shank Diameter:

Between 0.163 inches and 0.164 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Lubrication:

Cetyl alcohol

End Application:

Tactical vehicles

Grip Length:

0.563 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

1760 double pounds per square inch

Product Name:

Pin-riquet threaded, protruding head, hex point drive

Special Features:

Tension pounds 949; heat treat age to t6 condition per mil-h-6088; finish dye natural; dimensions after finish; surface texture per ansi b46.1 and hole preparation per hp3-2

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.