

View Online at <https://aerobasegroup.com/nsn/5320-01-476-1541>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.513 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

0.188 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.296 inches and 0.301 inches

Expansion Device:

Threaded stem

Lubrication:

Cetyl alcohol

End Application:

Tactical vehicles

Grip Length:

0.188 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-riquet, 100 degree flush shear head, cres, 10n vapor disposition coated

Special Features:

2coating detail, ivd disposition per mil-c-83488 type 2 except thickness .0003 when measured per mil-std-1312, tes 12, apra 4.1'cetyl alcohol lube per hi-shear spec305; shank diameter .188 min and .1895 max; rivet mates with hl70 collar

Material:

Stainless steel

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-83488 spec.