NSN 5320-01-476-1790

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-476-1790 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.628 inches and 0.648 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches **Head Minor Diameter:** Between 0.282 inches and 0.295 inches **Countersink Height:** Between 0.049 inches and 0.057 inches Lubrication: Cetyl alcohol **End Application:** C-17 aircraft **Grip Length:** Between 0.308 inches and 0.318 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or aams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear specification no 29 (hi-kote 1 only) mfr ref single treatment response

NSN 5320-01-476-1790

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0