# NSN 5320-01-476-1790

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-476-1790



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.628 inches and 0.648 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.010 inches and 0.015 inches

#### Width Between Flats:

Between 0.104 inches and 0.119 inches

#### Shank Diameter:

Between 0.2021 inches and 0.2026 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

#### Head Minor Diameter:

Between 0.282 inches and 0.295 inches

### **Countersink Height:**

Between 0.049 inches and 0.057 inches

#### Lubrication:

Cetyl alcohol

#### End Application:

C-17 aircraft

#### Grip Length:

Between 0.308 inches and 0.318 inches

#### Thready Qty Per Inch (tpi):

32

# Thread Size:

0.1900 inches

# **Countersink Angle:**

100.0 degrees

# Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4967 assn standard single material response or aams 4928 assn standard single material response

# Surface Treatment:

Aluminum

# Surface Treatment Specification:

Per hi-shear specification no 29 (hi-kote 1 only) mfr ref single treatment response

# NSN 5320-01-476-1790

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

