## NSN 5320-01-477-1654

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-1654 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.188 inches **Head Style:** Flush countersunk Width Between Flats: 0.240 inches **Shank Diameter:** Between 0.127 inches and 0.129 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.628 inches and 0.633 inches Lubrication: Cetyl alcohol **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 14600 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Ams 6415 assn standard all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 ty1 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5320-01-477-1654

Pin-rivet - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A528u0